



SANblade[®] QLE2462

Dual Port 4-Gbps Fibre Channel (FC) to PCI Express Host Bus Adapter (HBA)

High Performance

- 300,000 IOPS delivers high I/O transfer rates for storage applications
- Intelligent interleaved DMA (iiDMA) ensures maximum utilization of data links
- Out-of-Order Frame Reassembly (OoOFR) reduces congestion and retransmissions

Superior Scalability

- Multi-ID and N_Port virtualization ready. Allows physical ports to be part of multiple logical networks
- Cisco VSAN ready. Allows physical ports to be part of multiple logical networks
- Comprehensive Operating System (OS) driver support including Windows[®], Linux[™], Solaris[™], NetWare[®], and Mac OS[®]
- Universal boot support manages multiple hardware platforms and boot options

Enhanced Reliability

- Overlapping protection domains for continuous protection of internal data paths
- T10 Cyclic Redundancy Check (CRC) ensures end-to-end data integrity across Storage Area Networks (SANs)
- Three LEDs per port display real-time status and link activity information



QLE2462 Host Bus Adapter. The QLE2462 is the industry's first, true enterprise class, 4-Gbps to PCI Express x4 HBA. The QLE2462 not only delivers unprecedented levels of performance and availability, but also intelligent networking features specific to enterprise class data centers.

Enterprise Class Features. The QLE2462 HBA is the highest performing and most reliable HBA in the industry. It delivers unmatched performance by leveraging a single ASIC design, combining a unique hardware architecture to deliver over 300,000 IOPS, nearly 1.6 GBps throughput, and support for PCI Express x4 bus speeds. More importantly, the QLE2462 HBA provides new intelligent storage networking features that redefine the enterprise class HBA, providing increased data protection, advanced frame routing, and enterprise wide management capabilities.

Simplified Setup. Point-and-click installation and configuration wizards simplify the HBA setup process. Storage administrators can quickly deploy HBAs across a SAN using standard HBA management tools and device utilities. The QLE2462 is fully compatible with SNIA HBA API and SMI-S, thereby allowing administrators to manage QLogic HBAs using third-party software applications.

Comprehensive Operating System (OS) Support. QLogic offers the broadest range of support for all major operating systems to ensure OS and hardware server compatibility. Drivers are fully tested and available for all major operating systems and hardware server platforms. A single driver strategy per OS allows storage administrators to easily deploy and manage HBAs in heterogeneous SAN configurations.

Guaranteed Interoperability. Storage partner certifications, combined with agency and regulatory testing, ensures all products meet world compliance hardware and software specifications. All HBAs are tested extensively with third-party hardware, along with multiple software applications, to ensure best-in-class SAN interoperability and compatibility. You can be confident purchasing QLogic HBAs to meet your FC storage networking needs.

Investment Protection. For over 15 years, QLogic has been a technological leader with products that address the current needs of customers, yet provide strong investment protection to support emerging technologies and standards. QLogic stands alone in the industry with its product portfolio depth and experience in successfully delivering technological solutions that address the needs of today and tomorrow.

QLE2462

Host Bus Interface Specifications**Bus interface**

- PCI Express x4

Memory

- 1-MB SRAM per port, 1-MB flash (SPI), and 2-KB NVRAM (SPI)

Hardware platforms*

- IA32 (x86), IA64, IEM64T, AMD Opteron 64, Sun SPARC, Apple G5 (Xserve and Power Mac)

Compliance

- *PCI Express Base Specification*, revision 1.0a, *PCI Express Card Electromechanical Specification*, revision 1.0, *PCI Bus Power Management Interface Specification*, revision 1.1

Fibre Channel Specifications**Data rate**

- 4/2/1 Gbps auto-negotiation (4.2480/2.1240/1.0625 Gbps)

Performance

- 150,000 IOPS per port

Topology

- Point-to-point (N_Port), arbitrated loop (NL_Port), and switched fabric (N_Port)

Logins

- Support for F_Port and FL_Port login. 2,048 concurrent logins and 2,048 active exchanges per port

Class of service

- Class 2 and 3

Protocols

- FCP (SCSI-FCP), IP (FC-IP), FC-TAPE (FCP-2)

Compliance

- *SCSI-3 Fibre Channel Protocol (SCSI-FCP)*, *Fibre Channel Physical and Signaling Interface (FC-PH)*, *Fibre Channel 2nd Generation (FC-PH-2)*, *Third Generation Fibre Channel Physical and Signaling Interface (FC-PH-3)*, *Fibre Channel-Arbitrated Loop (FC-AL-2)*, *Fibre Channel Fabric Loop Attachment Technical Report (FC-FLA)*, *Fibre Channel-Private Loop Direct Attach Technical Report (FC-PLDA)*, *Fibre Channel Tape (FC-TAPE) profile*, *SCSI Fibre Channel Protocol-2 (FCP-2)*, *Second Generation FC Generic Services*

(FC-GS-2), *Third Generation FC Generic Services (FC-GS-3)*, *Fibre Channel Framing and Signaling (FC-FS)*

Physical Specifications**Ports**

- Dual 4-Gbps FC

Connections

- Small form factor fixed (SFF) multimode optic with LC-style connector

Form factor

- Low-profile PCI Express Card: 16.765 cm × 6.89 cm (6.6 in. × 2.713 in.)

Bracket size

- Standard: 1.84 cm × 12.08 cm (.73 in. × 4.76 in.)
- Low-profile: 1.84 cm × 8.01 cm (.73 in. × 3.15 in.)

Environment and Equipment Specifications**Airflow (no airflow required)****Temperature**

- Operating: 0°C/32°F to 55°C/131°F
- Storage: -20°C/-4°F to 70°C/158°F

Humidity

- Relative (non-condensing): 10% to 90%
- Storage: 5% to 95%

Power dissipation

- 6.5 W (maximum)

Cable distances

- 1 Gbps: 500 meters 50/125 µm fiber, 300 meters 62.5/125 µm fiber
- 2 Gbps: 300 meters 50/125 µm fiber, 150 meters 62.5/125 µm fiber
- 4 Gbps: 150 meters 50/125 µm fiber, 70 meters 62.5/125 µm fiber

Agency Approvals—Product Safety

US/Canada :UL, cUL: UL60950, CSA C22.2 No.60950, Class 1 Laser Product per DHHS 21CFR J

Europe

- 73/23/ECC Low Voltage Directive:
- TUV: EN60950-1: 2001, EN60825-1: 1994+A1+A2, EN60825-2: 1994 +A1

Agency Approvals—EMI and EMC

US : FCC Part 15, Class B

Canada: Industry Canada ICES-003, Class B

Europe: 89/336/EEC EMC Directive CE Mark, EN55022: 1998/CISPR22:1997 Class B, EN55024: 1998, EN61000-3-2:1995, EN61000-3-3:1994

Japan: VCCI, Class B

Taiwan: CNS 13438 Class B

New Zealand/Australia: AS/NZS 3548 Class B

Korea: MIC

Tools and Utilities**Management tools**

- SANsurfer FC HBA Manager

Device utilities

- Command line interface; utilities for firmware, driver, boot code, and NVRAM

Boot support

- BIOS, EFI, and FCode

APIs

- SNIA HBA API V2, SMI-S, and FDMI

Operating systems*

- Windows® Server™ 2003; Windows 2000; Windows XP Pro; Solaris 10; Linux Red Hat AS 3.0, 4.0; Linux SuSE SLES 8, 9; Novell NetWare 6.5; Mac OS X

Ordering Information**QLE2462-CK**

- Ships in an individually packed box with a standard size bracket and a spare low-profile bracket, FC HBA Manager CD, and Quick Start Guide

QLE2462-BK

- Ships in a bulk box in quantities of 20 and 50 with standard size brackets

*Subject to availability of OS and hardware from respective OEMs.



Corporate Headquarters QLogic Corporation 26650 Aliso Viejo Parkway Aliso Viejo, CA 92656 949.389.6000

www.qlogic.com

Europe Headquarters QLogic (UK) LTD. Surrey Technology Centre 40 Occam Road Guildford Surrey GU2 7YG UK +44 (0)1483 295825